

Elysee is an expanded, vinyl coated fabric featuring the industry-leading **PreFixx** protective finish and a woven, textile emboss. Versatile for a broad range of applications from contract interior seating to marine upholstery and other harsh outdoor environments.

Industries & Markets

- Corporate Office
- Food Service
- Healthcare
- Hospitality & Entertainment
- Retail
- Marine

End-Use Applications

- Contract Seating
- Dining Seating
- Medical Furnishings
- Guest room furnishings
- Lobby furnishings & millwork
- Spas & Health Clubs
- Theater Seating
- Retail Seating
- Coated Fabrics for Boats and Personal Watercraft

Physical Specifications

Weight (CFFA-700d)	30 oz/lin yd [20 oz/yd ²]
Weight, Metric (CFFA-700d)	850 g/lin m [567 g/m ²]
Width (CFFA-700a)	54 in. [137 cm]
Face Composition	PVC
Backing Description	Filament Polyester Knit
Roll Size	40 lin yd [37 lin m]
Emboss Level	Medium
Shipping Weight/ Roll	81 lb [37 kg]

Flame, Smoke & Toxicity

Meets or exceeds the following:	<ul style="list-style-type: none"> • Cal Tech 117-2013 Sec 1 • BIFMA - Class A • UFAC Fabric, Class 1 • NFPA 260 Class 1
---------------------------------	--

Performance Features

Protective Finish	PreFixx
Use	Indoor/Outdoor
QUV hours (minimum)	650
Adhesion #/in., min (CFFA-3)	3 Warp, 3 Fill
Tensile Strength #, min (CFFA-17)	85 Warp, 75 Fill
Tack Strength #, min (CFFA-14)	35 Warp, 30 Fill
Trap Tear Strength #, min (CFFA-16c)	20 Warp, 20 Fill
Wyzenbeek Abrasion (CFFA-1a)	1,300,000 Cotton Duck (double rubs)
Blocking (CFFA-4 No. 1)	Pass
W-Flex - 25,000 cycles (CFFA-10)	Pass
Crocking Resistance - 20 cycles no stain (CFFA-7)	Pass
Biocompatibility Certified ISO 10993-13	Pass
Fungal Resistance (ASTM-G-21)	Pass
Cold Crack (CFFA-6a)	-20 °F [-29 °C]
Compatible with Disinfectants	Yes. See Chem Resistance Tech Bulletin for more information.
Bleach-Safe	Yes, 10% Bleach Solution

Revision Date: 03-Oct-19

Note: Due to possible variances in your computer monitor, the colors and patterns displayed may vary slightly from the actual product. Customers should always obtain and compare actual samples before specifying.



Distributed by:
Arion EFV Ltd

100 John Street
Pukekohe 2120
New Zealand

P | 0800 644 445
F | 0800 65 99 00

All Arion EFV Ltd products and services are offered and sold subject to the Arion EFV Ltd standard terms and conditions of sale agreement. Trademarks are property of Arion EFV Ltd unless otherwise noted.
©2019 Arion EFV Ltd